

**Velox Top AF Neutral**

Date of compilation: 16/01/2014



Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Velox Top AF Neutral
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Disinfectant cleaner
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
MEDISEPT Sp. z o.o.
ul. Ludwika Spiessa 4
20-270 Lublin - lubelskie - Polska
Phone: +48 81 535 22 76
p.brewczak@medisept.pl
<https://medisept.pl/>
- 1.4 Emergency telephone number:** +48 81 535 22 92 at time: 8.00 a.m. – 4.00. p.m.
112 (general emergency number)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
Warning
-  
- Hazard statements:**
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
- Substances that contribute to the classification**
propan-2-ol
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**
Chemical description: Aqueous solution based on alcohols and surfactants.

- CONTINUED ON NEXT PAGE -



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX	propan-2-ol ¹ ATP CLP00		25 - <50 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	
CAS: 64-17-5 EC: 200-578-6 Index: 603-002-00-5 REACH: 01-2119457610-43-XXXX	ethanol ¹ Self-classified		10 - <25 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger	
CAS: 139734-65-9 EC: 701-317-3 Index: Non-applicable REACH: 01-2120050368-56-XXXX	Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid ¹ Self-classified		<1 %
	Regulation 1272/2008	Acute Tox. 3: H311; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; STOT RE 1: H372; STOT RE 2: H373 - Danger	
CAS: 7173-51-5 EC: 230-525-2 Index: 612-131-00-6 REACH: 01-2119945987-15-XXXX	Didecyltrimethylammonium chloride ¹ Self-classified		<1 %
	Regulation 1272/2008	Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Corr. 1B: H314 - Danger	

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
	Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	Acute
Didecyltrimethylammonium chloride CAS: 7173-51-5 EC: 230-525-2	Chronic	1
	Acute	10
	Chronic	1

Identification	Specific concentration limit
ethanol CAS: 64-17-5 EC: 200-578-6	% (w/w) >=50: Eye Irrit. 2 - H319

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

- CONTINUED ON NEXT PAGE -

**Velox Top AF Neutral**

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 4: FIRST AID MEASURES (continued)

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 0 °C
- Maximum Temp.: 25 °C
- Maximum time: 42 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	500 mg/m³	Non-applicable
ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	950 mg/m³	Non-applicable
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,86 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,19 mg/m³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	89 mg/m³	Non-applicable
ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	87 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	206 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	114 mg/m³	Non-applicable



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	Oral	Non-applicable	Non-applicable	0,029 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,286 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,047 mg/m³	Non-applicable

PNEC:

Identification				
propan-2-ol CAS: 67-63-0 EC: 200-661-7	STP	2251 mg/L	Fresh water	140,9 mg/L
	Soil	28 mg/kg	Marine water	140,9 mg/L
	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg
ethanol CAS: 64-17-5 EC: 200-578-6	STP	580 mg/L	Fresh water	0,96 mg/L
	Soil	0,63 mg/kg	Marine water	0,79 mg/L
	Intermittent	2,75 mg/L	Sediment (Fresh water)	3,6 mg/kg
	Oral	0,38 g/kg	Sediment (Marine water)	2,9 mg/kg
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	STP	0,22 mg/L	Fresh water	0,00031 mg/L
	Soil	0,726 mg/kg	Marine water	0,000031 mg/L
	Intermittent	0,000237 mg/L	Sediment (Fresh water)	1,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,18 mg/kg
Didecyl dimethyl ammonium chloride CAS: 7173-51-5 EC: 230-525-2	STP	0,14 mg/L	Fresh water	0,0011 mg/L
	Soil	1,4 mg/kg	Marine water	0,00011 mg/L
	Intermittent	0,00021 mg/L	Sediment (Fresh water)	61,86 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	6,186 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	60,95 % weight
V.O.C. density at 20 °C:	538,84 kg/m ³ (538,84 g/L)
Average carbon number:	2,65
Average molecular weight:	55,26 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	87 °C
Vapour pressure at 20 °C:	3513 Pa
Vapour pressure at 50 °C:	17705,2 Pa (17,71 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	879 - 889 kg/m ³
Relative density at 20 °C:	0,885
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	7,25 - 8,75
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Completely miscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	25 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	399 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	1,369 - 1,373

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: propan-2-ol (3); ethanol (1)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
propan-2-ol	5280 mg/kg		Rat
CAS: 67-63-0		12800 mg/kg	Rat
EC: 200-661-7		LC50 inhalation	Rat
		72.6 mg/L (4 h)	



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
ethanol CAS: 64-17-5 EC: 200-578-6	LD50 oral	6200 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	124,7 mg/L (4 h)	Rat
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	LD50 oral	756,6 mg/kg	Rat
	LD50 dermal	300 mg/kg (ATEi)	
	LC50 inhalation	Non-applicable	
Didecylidimethylammonium chloride CAS: 7173-51-5 EC: 230-525-2	LD50 oral	410 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
propan-2-ol CAS: 67-63-0 EC: 200-661-7	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
ethanol CAS: 64-17-5 EC: 200-578-6	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Algae
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Didecylidimethylammonium chloride CAS: 7173-51-5 EC: 230-525-2	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC	NOEC		
ethanol CAS: 64-17-5 EC: 200-578-6	NOEC	250 mg/L	Danio rerio	Fish
	NOEC	2 mg/L	Ceriodaphnia dubia	Crustacean
Didecylidimethylammonium chloride CAS: 7173-51-5 EC: 230-525-2	NOEC	Non-applicable		
	NOEC	0,021 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
propan-2-ol CAS: 67-63-0 EC: 200-661-7	BOD5	1,19 g O2/g	Concentration	100 mg/L
	COD	2,23 g O2/g	Period	14 days
	BOD5/COD	0,53	% Biodegradable	86 %
ethanol CAS: 64-17-5 EC: 200-578-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	89 %

- CONTINUED ON NEXT PAGE -



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	BOD5	Non-applicable	Concentration	5.17 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %
Didecyltrimethylammonium chloride CAS: 7173-51-5 EC: 230-525-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
propan-2-ol CAS: 67-63-0 EC: 200-661-7	BCF	3
	Pow Log	0.05
	Potential	Low
ethanol CAS: 64-17-5 EC: 200-578-6	BCF	3
	Pow Log	-0.31
	Potential	Low
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	BCF	19
	Pow Log	2.33
	Potential	Low
Didecyltrimethylammonium chloride CAS: 7173-51-5 EC: 230-525-2	BCF	71
	Pow Log	2.59
	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Koc	1.5	Henry	8,207E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes
ethanol CAS: 64-17-5 EC: 200-578-6	Koc	1	Henry	4,61E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,339E-2 N/m (25 °C)	Moist soil	Yes
Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid CAS: 139734-65-9 EC: 701-317-3	Koc	58119	Henry	Non-applicable
	Conclusion	Immobile	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 29*	detergents containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

- CONTINUED ON NEXT PAGE -



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number: UN1987
- 14.2 UN proper shipping name: ALCOHOLS, N.O.S. (propan-2-ol)
- 14.3 Transport hazard class(es): 3
Labels: 3
- 14.4 Packing group: III
- 14.5 Environmental hazards: No
- 14.6 Special precautions for user
Special regulations: 274, 601
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number: UN1987
- 14.2 UN proper shipping name: ALCOHOLS, N.O.S. (propan-2-ol)
- 14.3 Transport hazard class(es): 3
Labels: 3
- 14.4 Packing group: III
- 14.5 Marine pollutant: No
- 14.6 Special precautions for user
Special regulations: 274, 223
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- 14.1 UN number or ID number: UN1987
- 14.2 UN proper shipping name: ALCOHOLS, N.O.S. (propan-2-ol)
- 14.3 Transport hazard class(es): 3
Labels: 3
- 14.4 Packing group: III
- 14.5 Environmental hazards: No
- 14.6 Special precautions for user
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments: Non-applicable



Velox Top AF Neutral

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Composition of the active ingredients (Regulation (EU) No 528/2012): Didecyldimethylammonium chloride (0.26%); propan-2-ol (39.895%); ethanol (21.06%); Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid (0.65%)
 Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: propan-2-ol (Product-type 1, 2, 4) ; ethanol (Product-type 1, 2, 4) ; Amines, n-C10-16-alkyltrimethylenedi-, reaction products with chloroacetic acid (Product-type 2, 3, 4) ; Didecyldimethylammonium chloride (Product-type 1, 2, 3, 4, 8, 10, 11, 12)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Didecyldimethylammonium chloride

Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradability criteria stipulated in Regulation (EC) n°648/2004 on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

Labelling for contents:

Component	Concentration interval
Disinfectants	
Amphoteric surfactants	% (w/w) < 5

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H412: Harmful to aquatic life with long lasting effects.
- H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**Velox Top AF Neutral**

Date of compilation: 16/01/2014

Revised: 13/10/2021

Version: 8 (Replaced 7)

SECTION 16: OTHER INFORMATION (continued)**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H311 - Toxic in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

Aquatic Chronic 3: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:<http://echa.europa.eu><http://eur-lex.europa.eu>**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -